

# **PRODUCT SPECIFICATION**

**Customer : \_\_\_\_\_**

**Part No : XY-0805-1-OC**

**Developed No : \_\_\_\_\_**


**Date : \_\_\_\_\_**

CUSTOMER APPROVED BY

APPROVED	Q.C.	R&D

### 1. 外形尺寸 Dimensions

单位(Units): 毫米(mm)



#### 注意:

所有尺寸单位为 mm , 如无特殊说明误差范围为 ±0.05mm  
All dimensions are in mm tolerance is ±0.05mm unless otherwise noted.

### Typical Electrical & Optical Characteristics(Ta=25 °)

Items	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	VF	I <sub>F</sub> =20mA	1.9	2.1	2.3	V
Reverse Current	IR	VR =5V	---	---	5	µ A
Dominant Wavelength	d	I <sub>F</sub> =20mA	600	605	610	nm
Luminous Intensity	I <sub>V</sub>	I <sub>F</sub> =20mA	120	150	180	mcd
View Angle	2 1/2	I <sub>F</sub> =20mA	---	120	---	Deg

### Absolute Maximum Ratings (Ta = 25 )

Items	Symbol	Absolute maximum Rating	Unit
Power Dissipation	P <sub>D</sub>	120	mW
Forward Current(DC)	I <sub>F</sub>	30	mA
Peak Forward Current	I <sub>FP</sub>	120	mA
Reverse Voltage	V <sub>R</sub>	5	V
Operation Temperature	Topr	- 40 ~ + 85	
Storage Temperature	Tstg	- 40 ~ + 85	

## Typical Electrical/Optical Characteristics Curves:

