

SPECIFICATIONS

Current Rating: 3Amps
 Insulator resistance: 5000 Megohms min.
 Dielectric Withstanding: AC 500V
 Operating Temperature: -40° C to +105° C
 Insulator Material: PBT
 Plating: Tin flash


UNSPECIFIED TOLERANCE: ±0.20

DIMENSION TABLE:

POS	Dimension	
	DIM A/DIM B	DIM C.
2*3	15.22	5.080
2*4	17.76	7.620
2*5	20.30	10.16
2*6	22.84	12.70
2*7	25.38	15.24
2*8	27.92	17.78
2*9	30.46	20.32
2*10	33.00	22.85
2*11	35.54	25.38
2*12	38.08	27.94
2*13	40.62	30.46
2*14	43.16	32.98
2*15	45.70	35.56
2*16	48.24	38.10
2*17	50.78	40.64
2*18	53.32	43.18
2*19	55.86	45.72
2*20	58.40	48.26
2*21	60.94	50.80
2*22	63.48	53.34
2*23	66.02	55.88
2*24	68.56	58.42
2*25	71.10	60.96

PH2.54mm 筒牛 180度 2*NP

Customer:	Approval:	Unit	Scale	Date
Drawling:	Check:	mm		11.12.06



P/NO:
 Pin Longer:
 Signaturer: