

	1	2	3	4	5	6	7																																																																						
A								A																																																																					
B	<p>NOTES:</p> <ol style="list-style-type: none"> Material: <ol style="list-style-type: none"> 1.1 Housing: PBT+30%GF UL94V-0, Color White 1.2 Shell: Copper Alloy+ 1.3 Contact :Brass FINISH: <ol style="list-style-type: none"> 2.1 Contact Area: Selective Gold Flash <p>Solder Area: Tin Plated Under: Ni Plated</p> <ol style="list-style-type: none"> MECHANICAL: <ol style="list-style-type: none"> 3.1 Mating Force:3.57kgf Max. 3.2 Unmating Force:1.02kgf Min 3.3 Durability:1500 cycles Min ELECTRICAL: <ol style="list-style-type: none"> 4.1 Current Rating:1.5A 4.2 Dielectric Strength:500V AC FOR 1 MINUTE 4.3 Contact Resistance:30mΩ Max 4.4 Insulation Resistance:1000 MΩ Min 5. Operating temperature: -55°C TO +85°C 6.PACKIING: Tray 							B																																																																					
C	<p>RECOMMENDED P.C.B LAYOUT</p>							C																																																																					
D								D																																																																					
E								E																																																																					
F								F																																																																					
G	<p style="text-align: center;">RoHS compliant</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.20</td> <td>④</td> <td>Update</td> <td>08.06.2013</td> <td>Winnie</td> <td>Drawn</td> <td>04.05.2007</td> <td>Helwig</td> </tr> <tr> <td>X.XXX</td> <td>±0.100</td> <td>③</td> <td>Update</td> <td>07.07.2009</td> <td>Sterfanle</td> <td>Approved</td> <td>08.06.2013</td> <td>Winnie</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>To adapt</td> <td>11.09.2007</td> <td>N.Schulz</td> <td></td> <td></td> <td></td> </tr> <tr> <td>ANG.</td> <td>±1°</td> <td>①</td> <td>Production plant change</td> <td>04.05.2007</td> <td>Helwig</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Customer-No. _____ ASSMANN WSV-No. QT -USB SB Drawing-No. _____ rev04 SHEET</p>							Scale	Free							TOLERANCE								X.X	±0.3							X.XX	±0.20	④	Update	08.06.2013	Winnie	Drawn	04.05.2007	Helwig	X.XXX	±0.100	③	Update	07.07.2009	Sterfanle	Approved	08.06.2013	Winnie	DIM	TOL	②	To adapt	11.09.2007	N.Schulz				ANG.	±1°	①	Production plant change	04.05.2007	Helwig				Angle	TOL	Id.	Modification	Date	Name				G
Scale	Free																																																																												
TOLERANCE																																																																													
X.X	±0.3																																																																												
X.XX	±0.20	④	Update	08.06.2013	Winnie	Drawn	04.05.2007	Helwig																																																																					
X.XXX	±0.100	③	Update	07.07.2009	Sterfanle	Approved	08.06.2013	Winnie																																																																					
DIM	TOL	②	To adapt	11.09.2007	N.Schulz																																																																								
ANG.	±1°	①	Production plant change	04.05.2007	Helwig																																																																								
Angle	TOL	Id.	Modification	Date	Name																																																																								
H	<table border="1"> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> <td>7</td> </tr> </table>							1	2	3	4	5	6	7	H																																																														
1	2	3	4	5	6	7																																																																							
	131																																																																												