



剖面图 A-A

| 编号 | 修改原因 | 制图 | 审核 | 核准 |
|----|------|----|----|----|
| | | | | |
| | | | | |
| | | | | |

- Material And Plate
Screw:M2.5, Steel, Zinc-plating
Contact Material:Brass. Ni-Plated
Plastic Part: PA66, UL94V-0
- Mechanical Property
Temperature Range: -40 °C+105 °C
Transient Temperature :+250 °C 5S

Electrical

- Voltage: 300V
- Current: 10A
- Contact Resistance: 20m Ω
- Insulation Resistance: 5000M Ω/1000V
- Voltage Resistance: AC2000/1Min
- Wire Type: 24-12AWG 2.5mm
- Torsional Moment: 0.4Nm (3.6lb. in)

- WJ103- X X X X X
- 客户下板类型
R: 90° V: 180°
- 胶芯颜色
B: 蓝色 R: 红色
H: 黑色 G: 绿色
- 端子电镀规格
0: 半金锡 6: 全锡
Z: 镀锡
- 零件型号
S: 公头 P: 母座
- 产品Pin数
02/03-24

尺寸公差:

| | | | |
|-----|-------|-----|-------|
| X. | ±0.20 | X. | ±2° |
| .X | ±0.15 | .X | ±1.5° |
| .XX | ±0.10 | .XX | ±1° |

角度公差:

| | |
|-----|-------|
| X. | ±2° |
| .X | ±1.5° |
| .XX | ±1° |

| | | | |
|------|-----|------|----------|
| 投影法 | 第一角 | 品名 | 欧式接线端子 |
| 单位 | mm | 间距 | 5.00MM |
| 纸张尺寸 | A4 | 产品系列 | WJ103 系列 |



宁波万基特高电子有限公司
NINGBO WANJITEGAO CO.LTD

RECOMMEND PCB LAYOUT (TOLERANCE=±0.05)